



TECHNICAL DATA SHEET
v062015

ATF DIII

DESCRIPTION

Transmission fluid for automatic transmissions, power steering systems, torque converters and other applications requiring an ATF DIII fluid.

APPLICATION

Bardahl ATF DIII is particularly suitable for the transmissions (built after 1997) of passenger cars, delivery vans and trucks.

SPECIFICATIONS

This product offers the following performance level:

GM	DEXRON DIII F G (IIE, IID,B, AQ-ATF TypeA)
ZF	TE-ML 03D/ 04D/ 09B/ 11A/ 14B/ 17C
FORD	Mercon M2C-138CJ/ M2C-166H
VOLVO	97335-12
MAN	339F/ 339V1/ 339Z1
CAT	TO-2
ALLISON	C4
DAIMLER CHRYSLER	236.1/5/9
VOITH	G607/H55.6335.34
RENK	Doromat

PROPERTIES

- ✓ Has a low pour point.
- ✓ Offers a good stability.
- ✓ Is highly resistant against corrosion and oxidation.
- ✓ Provides anti-wear and antifoam properties.

SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



TECHNICAL DATA SHEET
v062015

ATF DIII

TECHNICAL DATA

Density at 20 °C	Kg/l	0,859
Viscosity at 40 °C	mm2/s	37,3
Viscosity at 100 °C	mm2/s	7,4
Viscosity at -40 °C	cP	<18000
Viscosity Index		169
Flash point COC, °C	°C	210
Pour point, °C	°C	-45

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36281	12 x 1 L
36288	20 L
36284	60 L
36237	205 L

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com