



TECHNICAL DATA SHEET
v062015

XTG 75W90

DESCRIPTION

Extreme pressure, synthetic, « Total Drive Line », gear oil formulated to lubricate manual transmissions and differentials submitted to difficult operating conditions (heavy loads, high speed and temperature).

APPLICATION

Bardahl XTG 75w90 is particularly suitable for heavy loaded hypoid differentials. Provides an excellent stability at different temperatures.

SPECIFICATIONS

This product offers the following performance level:

API	GL5
MACK	GO-G
MIL	MIL-L-2105D
MAN	342N 342 Type M1
ZF	TE-ML 05A/ 12A

PROPERTIES

- ✓ Offers a good resistance to high temperature.
- ✓ Provides very good extreme pressure (EP) properties.
- ✓ Has a low pour point.
- ✓ Provides a high resistance against corrosion and oxidation.
- ✓ Provides anti-wear and antifoam properties.

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



XTG 75W90

TECHNICAL DATA

Density at 20 °C	Kg/l	0,886
Viscosity at 40 °C	mm ² /s	82,6
Viscosity at 100 °C	mm ² /s	15
Viscosity index		192
Flash point COC, °C	°C	180
Pour point, °C	°C	-45

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36381	12 x 1 L
36383	3 x 5 L
36384	60 L
36387	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS