



TECHNICAL DATA SHEET
v062015

XTG CVT

DESCRIPTION

Very high performance fluid formulated for Continuously Variable Transmissions (CVTs). Suitable for CVT chain and CVT belt.

APPLICATION

Bardahl XTG CVT allows limiting fuel overconsumption on vehicles equipped with a CVT transmission.

SPECIFICATIONS

This product offers the following performance level:

BMW	83220136376/ 83220429159
MERCEDES	236.20
VW	G 052 180/ G 052 516
NISSAN	NS-1/ NS-2/ NS-3
HONDA	HMMF/ HCF2
MITSUBISHI	SPIII/ CVTF-J1
SUBARU	ECVT/ iCVT
DAIHATSU	AMIX CVT
SUZUKI	CVTF TC/ NS-2/CVT Green 1
HUYNDAI	SP-III
CHRYSLER JEEP	NS-2
TOYOTA	CVTF TC/FE
FORD	WSS-M2C928-A
JASO	M358
MOPAR	CVTF+4

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



XTG CVT

PROPERTIES

- ✓ Has a very low pour point.
- ✓ Has a very high and stable viscosity index.
- ✓ Performs well against friction.
- ✓ Provides antivibration performance
- ✓ Extends the fuel drain intervals.
- ✓ Provides a good resistance against oxidation and corrosion.
- ✓ Offers anti-wear, anti-foam and anti-shudder properties.

TECHNICAL DATA

Density at 15 °C	Kg/l	0,848
Viscosity at 40 °C	mm ² /s	35,4
Viscosity at 100 °C	mm ² /s	7,3
Viscosity Index		177
Flash point COC, °C	°C	214
Pour point, °C	°C	-48

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36501	12 x 1 L
36508	20 L

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com