



# XTS 0W40

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

Bardahl XTS 0w40 provides an excellent resistance against shearing. It is suitable for powerful engines, turbo-charged or not, with or without direct injection. Compatible with any type of fuel.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B4-12
API	SM/CF
MERCEDES BENZ	229.3
VW	502.00/505.00
BMW	Longlife-01
RENAULT	RN0700/RN0710
PORSCHE	A40

## PROPERTIES

- ✓ Offers a stable viscosity and a high Viscosity Index.
- ✓ Preserves the protective lubricating film at high temperature.
- ✓ Offers excellent dispersion and detergency properties.
- ✓ Makes cold start easier.
- ✓ Provides an excellent resistance against « shearing ».

### SADAPS BARD AHL ADDITIVES & LUBRICANTS



## XTS 0W40

### TECHNICAL DATA

Density at 15 °C	Kg/l	0,846
Viscosity at -35 °C	mPa.s	6000
Viscosity at 40 °C	mm <sup>2</sup> /s	83,7
Viscosity at 100 °C	mm <sup>2</sup> /s	14
Viscosity Index		173
Flash point COC, °C	°C	232
Pour point, °C	°C	-46
TBN Alcalinity	mgKOH/g	10,5
Sulphated Ash contents	%	1,33

### RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

36140	6 x 400 ML
36141	12 x 1 L
36143	3 X 5 L
36144	60 L
36147	205 L

#### SADAPS BARD AHL ADDITIVES & LUBRICANTS