



# XTS 0W20

## DESCRIPTION

New generation fully synthetic engine oil, developed to ensure a clean engine.

## APPLICATION

Bardahl XTS 0w20 improves fuel economy, increases piston cleanliness, reduces emissions, and protects against wear and the formation of muds. It can be used in turbo-charged hybrid-petrol engines. **It is compatible with E85 fuel.** Bardahl XTS 0w20 is suitable for modern hybrid vehicles.

## SPECIFICATIONS

This product offers the following performance level:

ILSAC	GF-5
API	SN, SN-RC
GM	6094M, DEXOS 1
CHRYSLER	MS 6395
FORD	WSS-M2C-945A/946A

## PROPERTIES

- ✓ Offers a stable viscosity and a high Viscosity Index.
- ✓ Provides a good resistance against « shearing ».
- ✓ Makes cold start easier.
- ✓ Offers an excellent resistance against oxidation.

### SADAPS BARDAHL ADDITIVES & LUBRICANTS



## XTS 0W20

### TECHNICAL DATA

Density at 20 °C	Kg/l	0,847
Viscosity at -35 °C	mPa.s	<6200
Viscosity at 40 °C	mm <sup>2</sup> /s	44,7
Viscosity at 100 °C	mm <sup>2</sup> /s	8,5
Viscosity Index		171
Flash point COC, °C	°C	210
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	8,5

### RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

36331	12 x 1 L
36333	3 x 5 L

#### SADAPS BARD AHL ADDITIVES & LUBRICANTS