



TECHNICAL DATA SHEET
v062015

XTM 15W50

DESCRIPTION

Mineral engine oil for passenger cars and delivery vans. Ideal for multi-fleet applications. Compatible with petrol, diesel and LPG cars, turbo-charged or not and equipped or not with a catalytic converter.

APPLICATION

Bardahl XTM 15w50 offers excellent cleaning properties and a very good protection against wear thanks to viscosity stabilizing additives. It also provides a good antirust and anticorrosion protection.

SPECIFICATIONS

This product offers the following performance level:

CCMC	G4/ D4/ PD-2
API	SG/SH/SJ CF-4
VW	501.00 / 505.00
MB	228.1
GM	6085-M
FORD	WSS M2C153-C
MIL	2104D/ 46152 EC

PROPERTIES

- ✓ Avoids deposits on pistons.
- ✓ Provides excellent cleaning properties.
- ✓ Offers anti-corrosion properties.

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



XTM 15W50

TECHNICAL DATA

Density at 20 °C	Kg/l	0,872
Viscosity at -20 °C	cP	<7000
Viscosity at 40 °C	mm ² /s	107,2
Viscosity at 100 °C	mm ² /s	14,6
Viscosity Index		140
Flash point COC, °C	°C	220
Pour point, °C	°C	-27
Sulphated ash contents	%	1,10

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36351	12 x 1 L
36353	3 x 5 L
36358	20 L
36354	60 L
36357	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS