OSRAM

LEDDRL301 CLAMP15

LEDriving PX-5 | – LED daytime running lights

Areas of application

- Daytime running light

Product benefits

- 3 year guarantee
- Low energy consumption
- Easy installation
- Suitable for many vehicle models
- Modern dotted diode effect
- Automatic dimming mode at night
- Dynamic appearance thanks to faceted optic and dotted LED technology
- Mountable into narrow bumper grids thanks to slim design and specific shape

Product features

- LED daytime running light
- Color temperature: up to 5,200 K
- Number of LEDs: 5
- Long lifetime: up to 5,000 h
- Certified according to ECE, SAE, CCC regulations
- Type of protection: IP67K

Technical data

Electrical data

Power input	13.5 W
Nominal voltage	13.2 V
Nominal wattage	12.5 W
Test voltage	14.0 V

Photometrical data

Color temperature	5200 K
Luminous flux	300 lm

Dimensions & weight

Length	160.0 mm
Product weight	552.00 g

Lifespan

Lifespan Tc	5000 h

Certificates & standards

Approval marks – approval	E4 approval

Country specific categorizations

Order reference	LEDDRL301 BK 12

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899170766	LEDDRL301 CLAMP15	Folding carton box 1	286 mm x 79 mm x 203 mm	4.59 dm³	762.00 g
4052899170773	LEDDRL301 CLAMP15	Shipping carton box 5	444 mm x 305 mm x 231 mm	31.28 dm³	4349.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Guarantee terms are available at
▶ www.osram.com/am-guarantee

Legal advice

ECE E4 approval
ECE R87 approval

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.